

CSA INTERNATIONAL
CERTIFICATION RECORD

The company named below has been authorized by CSA to represent the products listed in this record as "CSA Certified" and to affix the CSA Mark to these products according to the terms and conditions of the CSA Service Agreement and applicable CSA program requirements (including additional Markings).

File No: 014017 0 000

Class No: 5842 02 CORD SETS Power Supply Cords

SUBMITTOR

4504609

Electri-Cord Manufacturing Company
Incorporated
P.O. Box 167, 312 East Main St
Westfield, PA 16950
USA

FACTORIES

4504609

Electri-Cord Manufacturing Company
Incorporated
P.O. Box 167, 312 East Main St
Westfield, PA 16950
USA

4512749

Cordset Designs, Inc.
100 West New Street
Pink Hill, NC 28572
USA

4651645

E.S. Electri-Cord S.de R.L. de C.V.
El Bosque II Industrial Parque
Av Camino al Iteso 8499 Nave 5
Tlaquepaque, Jalisco
Mexico

December 4, 2001 (Replaces: March 15, 2001)

THE FOLLOWING COMPLIES WITH THE REQUIREMENTS OF CSA STD C22.2 NO 21-M90,
CLAUSE 6.23, FLEX TEST:

- Moulded (PVC) plug caps moulded on Nos 14 to 20 AWG, Types SPT-1, -2, -3, SPT-1 (NI), HPN, SJ, SJO, SJT (shielded or unshielded) and SVT (shielded or unshielded) flexible cord:
- 1-15P, Cat Nos MC-2, MC-6, MC-7, MC-31, MC-31P, MC-51, MC-51P, MC-T, MC-T-P.
- 5-15P, Cat Nos MC6-3, MC6-3 C/G, MCA-3-P, MC-3334
- 6-15P, Cat No MCA-3-T.
- Special-use plug, Cat Nos MC-C and MC-CP on No 18/2 AWG, Type SPT-2 flexible cord.
- PS cords, 10A, 125V, consisting of special use, 2-pole, 2-wire, male connector, Cat No BMC-11M or female connector, Cat No BMC-11F, moulded onto Certified No 18 AWG, Type SPT-2 flexible cords.

CSA INTERNATIONAL

Certification Record No: 014017 0 000

Class No: 5842 02

- Configuration 5-15P, Cat Nos MC6-3, MC6-3 C/G and MC-3334 on 14 to 18 AWG, Types SJT, HSJO, Certified flexible cord, 15A, 125V ac.
- PS cords consisting of attachment plug caps, moulded onto Nos 16 and 18 AWG, Types S and SO flexible cords, 5-15P configuration, Cat Nos MC-3334, MC6-3 and MCA-3P; 6-15P configuration, Cat No MCA-3T.
- Moulded or assembled g-use 1-15P plug caps, s-use plug caps and s-use female connectors on Nos 18/2-10/2 AWG and g-use 5-15P, 5-20P, 6-15P, 6-20P, L5-20P, L5-30P, L6-20P, L6-30P plug caps, s-use plug caps and s-use female connectors on Nos 18/3-10/3 AWG, Types S, SJ, SJO, SJOW, SJT, SJTO, SJTOW, SJTW, SO, SOW, ST, STO, STOW, STW, SV, SVO, SVT, flexible cords.
- PS cord with plug cap Cat No MC-62 on No 16 AWG, Type SJT
- PS cord with s-use female connector Cat No MFC-7 on No 18/2 AWG, SPT-1, -2 cords, rated 7A, 125V, 2.5A. 250V ac.
- PS cords consisting of a 5-15R configuration connector body, Cat No MFX-3, moulded onto Nos 14 AWG to 18 AWG, Type SJT flexible cord.
- PS cords incorporating general-purpose plug caps, Types 5-20P, 6-15P and locking plug caps, Types L5-15P, L5-20P, L6-15P, assembled onto No 18/3 AWG, Types SJT, SVT; No 16/3 AWG, Type SJT; No 14/3 AWG; Type SJT Certified flexible cords.
- PS cord with s-use male plug cap, Cat No HMB, on No 14/3 AWG (15A, 125/250V), Types SJT, SVT; No 16/3 AWG (13A, 125/250V) Types SJT, SJTshielded, SVT, SVT shielded; No 18/3 AWG (10A, 125/250V) Types SJT, SJT shielded, SVT, SVT shielded.
- PS cord with s-use male plug cap Cat No HMB-2 on Nos 14/2 (15A, 125/250V), 16/2 (13A, 125/250V), No 18/2 (10A, 125/250V) AWG, Types SJT, SJT 2 x No 18/2 AWG, Type SPT-2 flexible cords.
- Strain relief bushings, Cat Nos SR-Z369, SFR-B, moulded on Certified power supply cords, incorporating No 18 AWG, Type SPT-1, SPT-2 flexible cords.
- Strain relief bushings, Cat Nos BSR, BSR-F and S-BSR, moulded onto submittor's power supply cords, incorporating flexible cord, Types SPT-1, SPT-2, SJT and SVT, No 18 AWG.
- Strain relief bushings, Cat Nos SFR-R, SR-A, SR-E, SR-M, SR-MR and SR-P, moulded onto submittor's cords, or Types SPT-1 and SPT-2, No 18 AWG, flexible cords.
- Strain relief bushings, Cat Nos SR-L and SR-T, moulded onto submittor's power supply cords, incorporating flexible cord, Type SPT-1, No 18 AWG.
- Strain relief bushings, Cat Nos SFR-B3, SR-J and SR-RX, moulded onto submittor's power supply cords, incorporating flexible cord, Type SPT-2, No 18 AWG.
- Strain relief bushing, Cat No SR-093, moulded onto submittor's power supply cords, incorporating flexible cord, Types SPT-1, SPT-2 and SVT, No 18 AWG.
- Strain relief bushing, Cat No SR-125, moulded onto submittor's power supply cords, incorporating flexible cord, Type SVT, No 18 AWG.
- Strain relief bushing, Cat Nos SR-TR and SR-TR-130, moulded onto submittor's power supply cords, incorporating flexible cord, Types SJT, No 14 AWG and No 18 AWG.
- Strain relief bushing, Cat No SR-046, moulded onto submittor's power supply cords, incorporating flexible cord, Types SJT and SVT, No 18 AWG, and SJT, No 16 AWG.
- Strain relief bushing, Cat No SR-050, moulded onto submittor's power supply cords, incorporating flexible cord, Types SPT-1 and -2, No 18 AWG, and PLX and POXT, 20 AWG.
- PS cords with plug caps Cat No MCA520 (5-20P) and MCA620 (6-20P) moulded onto No 14 AWG Type SJT and SPT-3 flexible cords.

CSA INTERNATIONAL

Certification Record No: 014017 0 000

Class No: 5842 02

- PS cords with 5-15P, 5-20P, 6-15P, 6-20P plug caps, Cat No MC-9 on Nos 14/3-18/3 AWG, Types HSJO, S, SJ, SJO, SJT, SJT shielded, SO, ST, SVT, SVT shielded and Hospital Grade Cat No MC-9-H on Nos 12/3-18/3 AWG, Types HSJO, S, SJ, SJO, SJT, SJT shielded, SO, ST, SVT, SVT shielded flexible cords.
- PS Cords with 5-15P plug caps, Cat No MC-10 on Nos 14/3-18/3 AWG, Types HSJO, S, SJ, SJO, SJT, SJT shielded, SO, ST, SVT, SVT shielded Hospital Grade Cat No MC-10 on Nos 12/3-18/3 AWG, Types HSJO, S, SJ, SJO, SJT, SJT shielded, SO, ST, SVT, SVT shielded flexible cords.
- PS Cords with s-use female connector bodies, Cat Nos BME, BME-90L, BME-90LSC, BME-90L150, BME-90L150SC, BME-90L175SC, BME-90L175SC-S1, BME-90R, BME-90RSC, BME-90R150, BME-90R150SC, BME-90R175SC, BME-90R175SC-S1 and BME-1968 on No 14/3 AWG (15A, 125/250V), Type SJT, SJT shielded, SVT, SVT shielded, 16/3 AWG (13A, 125/250V), Type SJT, SJT shielded, SVT, SVT shielded, SPT-2; and No 18/3 AWG (10A, 125/250V), Types SJT, SJT shielded, SVT, SVT, SPT-1, -2 shielded flexible cords.
- PS Cords with s-use female connector bodies, Cat Nos BME-2, BME-90L-2, BME-90LSC-2, BME-90L150-2, BME-90L150SC-2, BME-90L175SC-2, BME-90L175SC-S1-2, BME-90R-2, BME-90RSC-2, BME-90R150-2, BME-90R150SC-2, BME-90R175SC-2, BME-90R175SC-S1-2 and BME-1968-2 on 14/2 AWG (15A, 125/250V), Type SJT, SVT, 16/2 AWG (13A, 125/250V), Types SJT, SPT-2, SVT and No 18/2 AWG (10A, 125/250V), Types SJT, SPT-1, -2, SVT flexible cords.
- PS cords with g-use 1-15P plug caps, s-use plug caps and s-use female connectors on Nos 18/2-14/2 AWG and g-use 5-15P, 5-20P, 6-15P, 6-20P plug caps, s-use plug caps and s-use female connectors may be moulded on Nos 18/3-14/3 AWG, Types S, SJ, SJO, SJOW, SJT, SJTO, SJTOW, SJTW, SO, SOW, ST, STO, STOW, STW, SV, SVO, SVT.
- PS Cord with a dual ground 5-15P Hospital Grade plug cap, Cat No MC-11 on No 16/4 AWG, Type SJO flexible cord.
- PS Cord with s-use female connectors Cat Nos BME-C19L, -C19R, -C19S on No 12/3 AWG (20A, 250V ac), 14/3 AWG (18A, 250V ac), No 16/3 AWG (13A, 250V ac), Types S, SJ, SJT, SJTW, ST, STW cords.
- PS Cord with s-use male plugs Cat Nos HMB-C20L, -C20R, -C20S on No 12/3 AWG (20A, 250V ac), 14/3 AWG (18A, 250V ac), No 16/3 AWG (13A, 250V ac), Types S, SJ, SJT, SJTW, ST, STW cords.

Notes:

1. Supplied only to manufacturers, as components, for the assembly of Certified electrical equipment, where the acceptability of the suitability of the combination in the end use is determined by CSA International.
2. The bonding conductor of Hospital Grade PS Cords longer than 3m must be No 16 AWG min.
3. The flexible cord types are permitted on the respective flexible cords sizes allowed by CSA International.

/jj

CSA INTERNATIONAL
CERTIFICATION RECORD

The company named below has been authorized by CSA to represent the products listed in this record as "CSA Certified" and to affix the CSA Mark to these products according to the terms and conditions of the CSA Service Agreement and applicable CSA program requirements (including additional Markings).

File No: 024378 0 000

Class No: 5841 03 CORD SETS Special-use Cord Sets

SUBMITTOR

4504609

Electri-Cord Manufacturing Company
Incorporated
P.O. Box 167, 312 East Main St
Westfield, PA 16950
USA

FACTORIES

4504609

Electri-Cord Manufacturing Company
Incorporated
P.O. Box 167, 312 East Main St
Westfield, PA 16950
USA

4512749

Cordset Designs, Inc.
100 West New Street
Pink Hill, NC 28572
USA

4651645

E.S. Electri-Cord S.de R.L. de C.V.
El Bosque II Industrial Parque
Av Camino al Iteso #8499 Nave #5
Tlaquepaque, Jalisco
Mexico

September 26, 2000 (Replaces: June 14, 2000)

- Cord sets incorporating bi-pin contactor bodies, Cat Nos 300TV, 350TV, 7A, 125V, assembled to the submittor's approved power supply cord incorporating a parallel blade attachment plug cap, for use with mixers, knives, etc.
- Special-use cord sets incorporating connector bodies, Cat Nos BMI-2 and BMI-3, 7A, 125V, assembled to the submittor's Certified power supply cords incorporating a parallel blade and grounding type attachment plug cap moulded on No 18 AWG, Type SJT, SVT, or POT flexible cord, for use on business machines.

CSA INTERNATIONAL

Certification Record No: 024378 0 000

Class No: 5841 03

- Special-use cord sets, rated 7A, 125V, incorporating connector body, Cat No BMI-3, assembled to the submitter's Certified power supply cords incorporating a CSA Certified 5-15P configuration attachment plug cap, hospital grade or general-purpose, on No 18/3 AWG, Types SJT and SVT flexible cords.
- Special-use cord sets consisting of connector bodies, Cat Nos BME, BME 3S, BME 90R, BME 90L, BME 90L150, BME 90R150, moulded onto submitter's Certified power supply cords incorporating Configurations 5-15P or 6-15P attachment plug caps, moulded onto Nos 18 AWG (10A, 125 or 250V), 16 AWG, (13A, 125 or 250V), Types SVT, SJT, No 14 AWG (15A, 125 or 250V), Type SJT, shielded or unshielded flexible cords.
- Special-use cord set consisting of a s-use female connection body, Series BME and a Certified 5-15P or s-use male plug cap moulded onto opposite ends of No 14/3 AWG (15A, 125/250V); 16/3 AWG (13A, 125/250V) and a No 18/3 AWG (10A, 125/250V), Types SJT, SJT shielded SVT shielded flexible cords.
- Special-use cord sets consisting of connector bodies, Cat Nos BME, BME3S, BME90R, BME90L, BME90L150 and BME90R150 moulded onto the submitter's Certified power supply cords incorporating a CSA Certified, 5-15P plug cap, hospital grade or general-purpose, or a L6-20P plug cap, or a 6-20P plug cap, assembled onto Nos 16/3 AWG (13A, 125 or 250V) and 18/3 AWG (10A, 125 or 250V), Types SJT and SVT, and No 14/3 AWG (15A, 125 or 250V), Type SJT flexible cords.
- Special-use cord set, 7A, 125V ac, 7A, 12V dc, consisting of connector body, Cat No 290-TV-AC, moulded to Certified power supply cord, 18 AWG Type SPT-2.
- Special-use cord set, 13A, 125V ac or 250V ac, incorporating connector body Cat No BME90S moulded onto submitter's Certified power supply cords incorporating attachment plug caps, assembled onto No 16 AWG (13A, 125 or 250V) Type SJT flexible cord.
- Special-use cord set, 10A, 125V; incorporating a special-use 2-pole, 3-wire female connector, Cat No WBH-F-3; moulded onto a CSA Certified power supply cord, consisting of a 5-15P configuration attachment plug cap, moulded onto No 18 AWG, Type SJT flexible cord. (Ref Report -27.)
- Special-use cord sets consisting of connector bodies, Cat Nos BME-90RSC, BME-90LSC, BME-90R150SC, BME-90L150SC, BME-90R175SC, BME-90R-175SC-S1, BME-90L175SC, moulded onto submitter's CSA Certified power supply cords, incorporating a 2-pole, 3-wire, grounding type attachment plug cap; moulded onto Nos 18 AWG (10A, 125 or 250V), 16 AWG (13A, 125 or 250V) Types SVT, SJT; No 14 AWG (15A, 125 or 250V) Type SJT, shielded or unshielded flexible cords. (Ref Report -25).
- Special-use cord set consisting of connector body, Cat No HMB, moulded onto submitter's CSA Certified power supply cords Nos 18 AWG (10A, 125/250V), Types SVT and SJT, regular and shielded; 16 AWG (13A, 125/250V), Type SJT, regular and shielded; 14 AWG (15A, 125/250V), Type SJT, regular only, flexible cords.
- Special-use cord sets, Cat Nos 300MD and 350MD, 3A, 125/250V, moulded onto CSA Certified Type SPT-1, No 18 AWG flexible cord.
- Special-use cord set, consisting of Certified, 5-15R configuration female connector body, Cat No MFX and Certified male power inlet connector body, Cat No HMB, for use with Certified Types SVT, SJT Nos 18, 16, 14 AWG flexible cord.
- Special-use cord set consisting of a s-use female connector body, Cat No MFC-7 and a Certified 1-15P or s-use male plug cap moulded onto opposite ends of No 18/2 AWG, Types SPT-1, -2, flexible cords (rated 7A, 125V).

DQD No. 548 99/04/08

Page 2

CSA INTERNATIONAL

Certification Record No: 024378 0 000

Class No: 5841 03

- Special-use cord set consisting of a s-use female connection body, Series BME and a Certified 5-15P or s-use male plug cap moulded onto opposite ends of No 14/3 AWG (15A, 125/250V), Types SJT, SJT shielded, SVT, SVT shielded; 16/3 AWG (13A, 125/250V), SJT, SJT shielded, SPT-2, SVT, SVT shielded and No 18/3 AWG (10A, 125/250V), Types SJT, SJT shielded, SPT-1, SPT-2, SVT, SVT shielded flexible cords.
- Special-use cord set consisting of a s-use female connector body, Series MBE-X-2 and a Certified 1-15P or s-use male plug cap moulded onto opposite ends of No 14/2 AWG (14A, 125/250V), Types SJT, SVT; No 16/2 AWG (13A, 125/250V), Types SJT, SPT-2, SVT and No 18/2 AWG (10A, 125/250V), Types SJT, SPT-1, SPT-2, SVT flexible cords.
- Special-use cord sets, consisting of: a Certified s-use female connector body and a Certified 1-15P or s-use male plug cap moulded or assembled onto opposite ends of No 18/2-12/2 AWG and Certified s-use female connector body and a Certified g-use 5-15P, 5-20P, 5-30P, 6-15P, 6-20P, 6-30P, L5-15P, L5-20P, L5-30P, L6-15P, L6-20P, L6-30P or s-use plug cap moulded or assembled onto opposite ends of Nos 18/3-12/3 AWG, Types S, SJ, SJO, SJOW, SJT, SJTO, SJTOW, SJTW, SO, SOW, ST, STO, STOW, STW, SV, SVO, SVT, SVTO flexible cords (rated 25A max, 250V max).
- Special-use cord set, with two s-use female connectors, Series BME, one splice Cat No RY-1 and one s-use male plug cap Series HMB moulded onto No 18/3 AWG, Type SVT flexible cords (rated 10A, 125/250V).
- Special-use cord set, with three s-use female connectors, Series BME, two splices Cat No RY-1 and one s-use male plug cap Series HMB moulded onto No 18/3 AWG, Type SVT flexible cords (rated 10A, 125/250V).

/sp

DQD No. 548 99/04/08

Page 3